ROAD SAFETY PRODUCTS

TEMPOLINE WR[®] | TEMPORARY ROAD MARKING TAPE

- TEMPORARY MARKING IDEAL FOR WORK ZONES
- SUPERIOR VISIBILITY AT NIGHT AND IN WET CONDITIONS
- AFFORDABLY PRICED
- MEETS EN 1436 & EN 1790 CRITERIA





TEMPOLINE WR TEMPORARY ROAD MARKING

PHYSICAL SPECIFICATIONS

	Type II P4	Type II P5	Type II P6	Type II P7
Daytime reflectivity Qd	Q4	Q3	Q3	Q5
Retroreflectivity RL (WET)	R3	R4	R5	R5
Retroreflectivity RL (DRY)	RW3	RW4	RW4	RW3
Skid Resistance S	S1	S2	S1	S1
Application Temperature Range	10° - 35°C			
Relative Humidity	< 70%			
Application Method	Primer			
Available Colors	Yellow			

EASY TO INSTALL, EASY TO REMOVE

TEMPOLINE WR consists of a flexible rubber layer, reinforced with polyester fabric to assure effective removal. Upper surface texture and special glass beads provide superior visibility at night and in wet conditions, in fact, high levels of reflectivity are assured in all weather and lighting conditions. TEMPOLINE WR Temporary tape is ideal for traffic deviations and temporary symbols in construction zones, where high visibility is required.

FREQUENTLY ASKED QUESTIONS

How long does Tempoline WR last?

TEMPOLINE WR is designed to ensure high quality road markings for a long time.

Real durability depends on traffic and climatic conditions. Usual application for work zones lasts 6 – 12 months.

How can you mantain it?

Where marking is damaged, TEMPOLINE WR can be patched after cleaning the surface and following the application techniques.

How do you store Tempoline WR?

Tape and primer must be stored in a cool and dry area indoors and used within 18 months from delivery.

Primer contains flammable solvents: handle with care.

FEATURES

- Superior visibility at night and in wet conditions
- No harmful pigments based in cadmium, chromium, or lead
- Fast and easy application & removal
- Tested and approved in several European Countries
- Different Roll-over classes available for different traffic conditions
- Road can be opened to traffic as soon as application is finished
- Available in many widths

WHERE TO USE

- As a longitudinal stripe to indicate a temporary lane change
- Temporary symbols in construction zones

Optional Tape Application Systems are available for to make road marking deployment even easier.

DISTRIBUTED BY:









Snoline spa

Via F. Baracca 19/23 • 20056 Trezzo sull'Adda (MI) • Italia • Tel. +39 02909961 • e-mail: info@snoline.com General details for the TEMPOLINE WR are subject to change without notice to reflect improvements and upgrades. Additional information is available from Snoline S.P.A. © Lindsay Transportation Solutions