DEFLEX | LANE SEPARATOR

- IDEAL FOR DELINEATING EXITS, VIABILITY CHANGES AND CENTRELINES
- EASY TO INSTALL
- HIGH VISBILITY AND DURABILITY









PHYSICAL SPECIFICATIONS

	Vertical cylindrical delineator	Hexagonal base
Height	325 mm	-
Diameter	66 mm	250 mm
Standard color	Yellow RAL 1003 - Red RAL 3020	Black

The base block has to be ordered separately, because it is not included in the consignment.

DESCRIPTION

DEFLEX is a cylindrical flexible delineator of red or yellow colour. A hexagonal black base block is used to fix it to the pavement. The cylindrical body is set with 3 retroreflective inserts of class 1 or class 2 film. It is suited to delineate work zones, road works, deviations, channelling and separations between opposite driving sections. The colour shall be paste-dyed yellow, capable of guaranteeing permanence of the colour.

GENERAL CONDITIONS OF APPLICATION

DEFLEX is fixed to the ground by means of mechanical fixing methods. More details and information in the placing instruction. Considering the technical-physical features of the raw material DEFLEX keeps his function with different temperatures, from -30 to 70 °C.

PRODUCT LIFE

DEFLEX is designed to obtain excellent results for a long period. Obviously, his effective life depends on traffic and climate conditions.

MAINTENANCE

In case of incident and/or impact check if DEFLEX structure is undamaged and replace the damaged parts where necessary.

CHARACTERISTICS

DEFLEX is obtained by moulding paste-died polyurethane. Given the particular material features DEFLEX offers excellent strength and resistance to abrasion, weatherability and colourfastness.

STORAGE

Particular conditions of temperature and humidity are not required, but are necessary that this product is stored without causing strain or bending points so that the structure linearity will not be compromised.

DISTRIBUTED BY:







